


R135

SKID LOADERS



GEHL®

Capacities		Metric	Imperial
Rated Operating Capacity		612 kg	1349 lb
Rated Operating Capacity with Optional Counterweight		680 kg	1499 lb
Unladen weight		2327 kg	5130 lb
Weight and dimensions			
Overall Operating Height - Fully Raised	h27	3653 mm	144 in
Height to Hinge Pin – Fully Raised	h28	2790 mm	110 in
Overall Height to Top of ROPS	h17	1930 mm	76 in
Dump angle at full height	a5	40 °	40 °
Dump height	h29	2120 mm	83 in
Overall length with bucket	l16	3048 mm	120 in
Dump reach - Full height	r6	591 mm	23 in
Rollback at ground		28 °	28 °
Seat to ground height	h30	846 mm	33 in
Wheelbase	y	950 mm	37 in
Overall width less bucket	b1	1364 mm	54 in
Bucket Width	e1	1372 mm	54 in
Ground clearance	m4	201 mm	8 in
Overall length - Less Bucket	l2	2322 mm	91 in
Clearance Radius - Front with Bucket	b18	1842 mm	73 in
Clearance Circle - Front without Bucket	b19	1120 mm	44 in
Clearance Circle - Rear	wa1	1372 mm	54 in
Performances			
Travel speed (unladen)		12.90 km/h	8 mi/h
Wheels			
Standard tyres		10.00x16.5 HD	10.00x16.5 HD
Engine			
Engine brand		Yanmar	Yanmar
Engine model		4TNV88C	4TNV88C
Engine norm		Stage V / Tier 4	Stage V / Tier 4
Gross Power (kW)		34.30 kW	34.30 kW
Net Power (kW)		33.20 kW	33.20 kW
Max. torque / Engine rotation		146.20 Nm / 2800 rpm	146.20 Nm / 2800 rpm
Battery		12 V	12 V
Starter (kW)		2.30 kW	2.30 kW
Hydraulics			
Standard flow - Auxiliary hydraulics		70 l/min	70 l/min
Tank capacities			
Fuel tank		59.40 l	16 US gal
Displacement		2.19 l	0.58 US gal
Noise and vibration			
Environmental noise (LWA)		101 dB	101 dB
Whole-Body Vibration (ISO 2631-1)		0.81 m/s ²	0.81 m/s ²
Vibration to whole hand/arm		< 1.77 m/s ²	< 1.77 m/s ²



GEHL®

Siège Social
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095
Tel: (262) 334-9461 - Fax: (262) 338-7517
www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend